



Kelvin Imports

Kelvin Engineering limited. Field view
business centre, Newchapel Road,
lingfield,Surrey, RH7 6LE

www.kelvinengineering.co.uk



2022 VERSION 2/COPYRIGHT 2022/06

KELVIN ENGINEERING reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.



**XF Series Diesel / Gasoline / LPG
Counterbalanced Trucks**

with capacities of 1,000 to 3,500kg

Kelvin will be with you at every stage

Efficient, reliable solutions for your demands



GCT

Eco-friendly engines compliant with global emission regulations.
Global standard forklift engines with top-class of output and reliability performance.

ENGINE TYPE	Vertical Inline 4-cylinder • Water cooled• OHV
FUEL	Gasoline •LPG
FUEL SYSTEM	Electronic Controlled, Gasoline : Injector• LPG : Injector
EMISSION REGULATION	CARB SIP LSI-1/ EPA Tier2/ EU STAGE V



Interactive instrument: The instrument adopts 4.0-inch colour LCD display with four interactive buttons, and has one CAN bus communication function. The communication protocol is compatible with CANopen and SAE J1939 standards.

No.	Capacity	Series	Manufacturer	Engine	Drive power	Model	Emission Std.	Transmission	Power (kw/rpm)
1	1.0-1.75t	XF	GCT	GCT GK21LPG EU-StageV CERT	LPG	CPYD15/18-XH1F/B	Stage V	F/OKAMURA	38.4/2700
2	2.0-3.5t	XF	GCT	GCT GK25LPG EU-StageV CERT	LPG	CPYD20/25/30/35-XH3F/B	Stage V	F/OKAMURA	43.4/2700
3	1.5-1.75t	XF	GCT	GCT GK21 LPG 1G001 EKH00	LPG	CPYD15/18-XH23F/B1	CARB SIP LSI-1/ EPA Tier2/ EU STAGE V	F/OKAMURA	43/2700
4	1.5-1.75t	XF	GCT	GCT GK21 DUAL 1G001 ECH00	DUAL LPG/GAS	CPQYD15/18-XH24F/B1		F/OKAMURA	43/2700 40/2700
5	2.0-3.5t	XF	GCT	GCT GK25 LPG 1G001 ELH00	LPG	CPYD20/25/30/35-XH21F/B1		F/OKAMURA	47/2700
6	2.0-3.5t	XF	GCT	GCT GK25 DUAL 1G001 EDH00	DUAL LPG/GAS	CPQYD20/25/30/35-XH22F/B1		F/OKAMURA	47/2700 44.5/2700

Note: Stage V applied for European Union also including Israel and Turkey
Tier4 Final applied for North American
F means full floating transmission


STAGE V & TIER 4F

With Kelvin you can meet all Stage V/Tier 4f emissions standards which provides customer demands for value, innovation and performance. The technologies include common rail fuel systems, diesel oxidation catalysts (DOC) and diesel particulate filters (DPF). Designed and optimised to every engine model, our forklift truck maximises efficiency and reliability.



KUBOTA

- Emissions Compliance
Meeting rigid emissions regulations can be a challenge for any company. V2607-CR-E5B engines have been designed to comply with stringent regulations: EU StageV EPA/CARB Tier4 F.
- Advanced DPF Technology
- Clean and Quiet Power
- Great Flexibility



XINCHAI

No.	Capacity	Series	Manufacturer	Engine	Drive power	Model	Emission Std.	Transmission	Power (kw/rpm)
1	1.5-3.5t	XF	KUBOTA	V2607-CR-E5B	Diesel	CPCD15/18/20/25/30/35-XW97F	EU StageV EPA/CARB Tier4 F	F	37.4/2400
2	2.0-3.5t	XF	KUBOTA	V2607-CR-TE5B	Diesel	CPCD20/25/30/35-XW98F	EU StageV EPA/CARB Tier4 F	F	47.3/2400
3	1.5-1.75t	XF	XINCHAI	3E22YG51P464	Diesel	CPCD15/18/-XH7F	Stage V	F/OKAMURA	34/2400
4	2.0-3.5t	XF	XINCHAI	3E22YG51	Diesel	CPCD20/25/30/35-XH7F/B	Stage V	F/OKAMURA	44.8/2400

Note: Stage V applied for European Union also including Israel and Turkey
Tier4 Final applied for North American
F means full floating transmission




Productivity

Dynamic load sensing hydraulic steering system, Efficiency lighting system, lower fuel consumption, combine to provide increased productivity and reduced operating costs.


The new Dynamic load sensing hydraulic steering system contributes to reduce loss of hydraulic and improve energy efficiency.

The new efficiency lighting system employs LED illuminant and new type reflector to reduce energy consumption, improve significantly illumination performance and prolong work time.


By optimizing transmission design, the power train provides higher efficiency. The fuel consumption is reduced by 10%.



Hydraulic oil balanced temperature (2.5T 4TNE98)



Fuel consumption



Speed at full load (2.5T 4TNE98)

Comfortable Operation



In developing the new XF Series, comfort and ease of operation is carefully considered, for example, to improve vibration levels, compound engine damper and full floating power train are adopted. Comfortable operating environments for operator also contribute to increased productivity.



In addition to rubber damper between frames and steering axle, compound engine damper and full floating power train achieve flexible connection between frames and driving system, as a result, traveling vibrations and vibrations from the driving system are significantly reduced.




The enlarged capacity of optimized exhaust muffler, the intake muffler and the noise shield technologies provide significantly lower noise levels.

1. The new, relocated easy- to-see LCD meter lets the operator check on all aspects of operational status at a glance.
2. The new automobile-style light/turn-signal lever and forward-reverse lever are ergonomically designed and arranged to improve comfort and productivity.
3. The small diameter steering wheel with tilt adjustment provides the ideal operating position. The superior responsiveness of the steering wheel optimizes maneuverability even in narrow spaces.
4. The parking brake is specially developed. The operational force is reduced by 30%.
5. The automobile-style suspended pedals provide more ergonomic operation.



Comfortable Operation

Optimal visibility in all directions create the best conditions for high productivity through relaxed and safe working.



The extra foot space is provided to reduce operator fatigue significantly. The new wide-open, non-slip step makes getting in and out easy and safe.

The optional Electro-hydraulic proportional control system contributes more sensitive and precise load handling. The easy- to-operate levers provide total load handling operation. An armrest is provided to reduce fatigue.

In addition to the soft landing system, the soft lifting system is adopted (front lifting cylinders of triplex mast and full free duplex mast), as a result, the noise and shock of the mast significantly decreases.



The developed front lifting cylinders with smaller outer diameter give the operator superior forward visibility.

The double lifting cylinders provide better forward visibility.

Reliability

By focusing on enhancing reliability, reducing downtime, the XF series is able to make the greater productivity for customer.



The new aluminum alloy transmission with full floating structure features excellent heat dissipation capability, more and thicker disc meet the most demanding applications.



The new vehicle controller integrates all electrical components, features excellent durability for temperature, water and vibration for most demanding operation.



The new stamped air cleaner featuring tangential intake, double seal with safety filter is durable, corrosion-free and vibration-resistant, provides better filter efficiency and lower intake resistance than the previous.



XF series features rugged design, stamped frame and engine hood, stamped instrument panel and head guard, heavy profile rail mast combine to provide excellent rigidity, which ensures outstanding reliability even in heavy-duty work.



Extra capacity combined radiator with serpentine wave and optimized heat dissipation channel enhance the heat dissipation capability to keep engine reliability even in heavy-duty applications.

Easy Maintenance



Careful design facilitates inspection and servicing. Easy maintenance reduces the amount of downtime and helps to reduce cost also.

The cover on the Panel can be lifted up simply to check the brake fluid.

The two-piece design makes the floorboard easy to lift and remove for access to the power train.

The easy-to-operate latch provides quick access to the engine compartment.

The fasteners of the radiator cover can be turned easily by hand to enable quick inspections or servicing.

Safety

A wide range of technologies are applied to ensure absolute safety for both the operator and those in the surrounding.



The locking device of the engine hood damper and parking brake help add to safety.



An optional rear-pillar assist grip with a horn button enhances safety of operator while traveling in reverse.



1. The operator presence sensing system incorporates lifting/tilting and traveling locking function. When the operator leaves the seat, the system automatically locks lifting / tilting and disables traveling to ensure safety.
2. A throttling device is adopted to avoid the mast being out of control even some pipes are broken.

Standards

Transmission	Steering	Chassiss	Control	Hydraulic
/ Suspended transmission / Oil filter / Dipstick / Oil cooler / Non-asbesttos brake / MS transmission with wet bral:e	/ Full hydraulic power steering / Smaller diameter steering wheel / Adjuster of steering wheel	/ Skidproof pedal / Rubber pedal / Engine hood spring	/ Power steering / Suspension pedal / Integrated combination switch / Cable parking brake	/ Dynamic load sending control valve (Diesel IC) / Hydraulic oil filter / Tilt cylender self-locking valve / Hydraulic oil dipstick
Truck	Power	Electronics	Mast	
/ Traction device / Handhilds / Standard seat / Standard overhead guard / Waterproof cover on the guard / Back view mirror / Pneumatic tyres / Toolbox	/ Big capacity aluminum radiator / Little tank / Whirlwind air cleaner / Safety filter / High-efficient intake muffler / High-efficient exhaust muffler	/ High-efficient front lights / High-efficient LED rear lights / Service-free start battery / Combination controller / LCD display / Neutual switch / Time meter / Fuel gauge / Water temperature gauge / Pre-heat indicator / Charging indicator / Engine fuel pressure warning / Transmission oil pressure warning / Horn / Reversing buzzer / Power off	/ Standard wide view duplex mast / Standard forks / Standard fork carriage / Standard load back rest / Mast speed limiting valve / Load safety valve / Mast down buffer device / Mast up buffer device / Side roller	

Options

Truck	Transmission	Power	Hydraulic	Electronics	Mast
/ Cabin / Cabin heater / Front window / Super elastic tyre / No-mark tyre (white/green) / Suspension seat / Extinguisher / Cover of tilt cylender / Heightening overhead guard / Reversing assist grip / Special given color / Seat with sensing system / Boot for tilt cylinder / Counter weight net	/ 2-D wheel	/ Duel fuel LPG system / Big capacity copper radiator / High-positioned exhaust system / Middle-positioned exhaust system / Air pre-cleaner / Net cover of radiator / Sparkle arrester / Purified exhaust system / Swiwel LPG bottle support / Downward LPG bottle support / Fan protector	/ Auxiliary hydraulic valve / Electro-hydraulic proportional control system / Return oil filter	/ OBD / Front working light / Rear working light / Warning lamp / Oil-water seperator warning	/ Duplex wide view free-lift mast / Triplex wide view free-lift mast / Triplex wide view 4-cylinder free-lift mast / Special forks / Wider fork carriage / Wider load back rest

Optional Attachments

- / Paper roll clamp

/ Rotating bale clamp

/ Load stabilizer

/ Multi-drum clamp

/ Bale clamp

/ Drum clamp

/ Dumping clamp

/ Crane arm

/ String Pole
- / Sideshifter

/ Rotating forks

/ Fork extensioner

/ Load release device

/ Carton clamp

/ Push-pull device

/ Bucket

/ Hook

/ Lengthened fork



XF series 1.0-3.5t forklift specification:

Distinguishing mark	1.1	Importer		KELVIN														
	1.2	Manufacturer's type designation		CPCD10-XW32F/B	CPYD15-XH1F/B	CPCD15-XH7F	CPCD15-XW97F	CPYD18-XH1F/B	CPCD18-XH7F	CPCD18-XW97F	CPYD20-XH3F/B	CPCD20-XH7F/B	CPYD25-XH3F/B	CPCD25-XH7F/B	CPYD30-XH3F/B	CPCD30-XH7F/B	CPYD35-XH3F/B	CPCD35-XH7F/B
	1.3	Drive: electric (battery or mains), diesel, petrol, fuel gas		Diesel	LPG	Diesel	Diesel	LPG	Diesel	Diesel	LPG	Diesel	LPG	Diesel	LPG	Diesel	LPG	Diesel
	1.5	Rated capacity/rated load	Q (kg)	1000	1500	1500	1500	1750	1750	1750	2000	2000	2500	2500	3000	3000	3500	3500
	1.6	Load centre distance	c (mm)	500	500	500	500	500	500	500	500	500	500	500	500	500	500	500
	1.8	Load distance, centre of drive axle to fork	x (mm)	405	405	405	405	405	405	405	465	465	465	465	480	480	485	485
		Rear overhang	mm	375	405	405	405	430	430	430	415	415	490	490	550	550	615	615
	1.9	Wheelbase	y (mm)	1475	1475	1475	1475	1475	1475	1475	1650	1650	1650	1650	1700	1700	1700	1700
Weight	2.1	Service Weight	kg	2510	2650	2650	2650	2760	2760	2760	3405	3405	3765	3765	4350	4350	4705	4705
	2.2	Axle loading, laden front/rear	kg	3055/455	3660/490	3660/490	3660/490	3995/520	3995/520	3995/520	4705/700	4705/700	5475/790	5475/790	6450/900	6450/900	7255/950	7255/950
	2.3	Axle loading, unladen front/rear	kg	1260/1250	1240/1410	1240/1410	1240/1410	1225/1540	1225/1540	1225/1540	1610/1795	1610/1795	1560/2205	1560/2205	1750/2600	1750/2600	1720/2985	1720/2985
Tyres, chassis	3.2	Tyre size, front		6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	7.00-12-12PR	7.00-12-12PR	7.00-12-12PR	7.00-12-12PR	28x9-15-14PR	28x9-15-14PR	28x9-15-14PR	28x9-15-14PR
	3.3	Tyre size, rear		5.00-8-10PR	5.00-8-10PR	5.00-8-10PR	5.00-8-10PR	5.00-8-10PR	5.00-8-10PR	5.00-8-10PR	6.00-9-10PR	6.00-9-10PR	6.00-9-10PR	6.00-9-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR
	3.6	Tread, front	b10 (mm)	900	900	900	900	900	900	900	965	965	965	965	1005	1005	1005	1005
Dimensions	3.7	Tread, rear	b11 (mm)	920	920	920	920	920	920	920	973	973	973	973	975	975	975	975
	4.1	Tilt of mast/fork carriage forward/backward	α/β(°)	6/12	6/12	6/12	6/12	6/12	6/12	6/12	6/12	6/12	6/12	6/12	6/12	6/12	6/12	6/12
	4.2	Height, mast lowered	h1 (mm)	1995	1995	1995	1995	1995	1995	1995	2035	2035	2035	2035	2050	2050	2165	2165
	4.3	Free lift	h2 (mm)	155	155	155	155	155	155	155	140	140	140	140	145	145	145	145
	4.4	Lift	h3 (mm)	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000
	4.5	Height, mast extended	h4 (mm)	3955	3955	3955	3955	3955	3955	3955	4045	4045	4045	4045	4145	4145	4145	4145
	4.7	Height of overhead guard (cabin)	h6 (mm)	2125(2205*)	2125(2205*)	2125(2205*)	2125(2205*)	2125(2205*)	2125(2205*)	2125(2205*)	2135(2215*)	2135(2215*)	2135(2215*)	2135(2215*)	2150(2230*)	2150(2230*)	2150(2230*)	2150(2230*)
	4.20	Length to face of forks	l2 (mm)	2255	2285	2285	2285	2310	2310	2310	2530	2530	2605	2605	2730	2730	2800	2800
	4.21	Overall width	b1 (mm)	1080	1080	1080	1080	1080	1080	1080	1155	1155	1155	1155	1225	1225	1225	1225
	4.22	Fork dimensions	s/e/l (mm)	920x100x35	920x100x35	920x100x35	920x100x35	920x100x35	920x100x35	920x100x35	1070x122x40	1070x122x40	1070x122x40	1070x122x40	1070x122x45	1070x122x45	1070x122x50	1070x122x50
	4.31	Ground clearance, laden, below mast	m1 (mm)	115	115	115	115	115	115	115	115	115	115	115	130	130	130	130
	4.32	Ground clearance, centre of wheelbase	m2 (mm)	140	140	140	140	140	140	140	150	150	150	150	165	165	165	165
	4.35	Turning radius	Wa (mm)	1965	1990	1990	1990	2015	2015	2015	2180	2180	2245	2245	2355	2355	2415	2415
		Min. right angle stacking aisle width (Add load length and clearance)	mm	2370	2395	2395	2395	2420	2420	2420	2645	2645	2710	2710	2835	2835	2900	2900
Performance data	5.1	Travel speed, laden/unladen	km/h	(-/19)(-/19.3)(-/19)	(-/20)	(-/20)	(-/19)	(-/20)	(-/20)	(-/19)	(-/20)	(-/18.5)	(-/20)	(-/19)	(-/19.8)	(-/18.5)	(-/19.8)	(-/18.5)
	5.2	Lift speed, laden/unladen	m/s	0.580/-	0.530/-	0.580/-	0.680/-	0.530/-	0.580/-	0.680/-	0.560/-	0.600/-	0.560/-	0.600/-	0.480/-	0.480/-	0.480/-	0.440/-
	5.3	Lowering speed, laden/unladen	m/s	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-
	5.5	Drawbar pull, laden/unladen	N	(14600/-)(14400/-)(14100/-)	(19000/-)	14500/-	16800/-	(19000/-)	14500/-	16800/-	(21000/-)	19500/-	(21000/-)	19500/-	(22000/-)	20500/-	(22000/-)	20500/-
	5.7	Gradeability, laden/unladen*	%	(40/-)(39/-)(38/-)	(37/-)	29/-	34/-	(37/-)	29/-	34/-	(30/-)	27/-	(30/-)	25/-	(25/-)	23/-	(25/-)	23/-
Combustion-engine	7.1	Engine manufacturer/type		YANMAR/4TNE92	GCT GK21 LPG EU StageV	3E22YG51P464	KUBOTA V2607-CR-E5B	GCT GK21 LPG EU StageV	3E22YG51P464	KUBOTA V2607-CR-E5B	GCT GK25LPG EU StageV	XINCHAI 3E22YG51	GCT GK25LPG EU StageV	XINCHAI 3E22YG51	GCT GK25LPG EU StageV	XINCHAI 3E22YG51	GCT GK25LPG EU StageV	XINCHAI 3E22YG51
		Emission STD		StageIIIA/Tier3	EU StageV	EU StageV	EU StageV EPA/CARB Tier4 F	EU StageV	EU StageV	EU StageV EPA/CARB Tier4 F	EU StageV	EU StageV	EU StageV	EU StageV	EU StageV	EU StageV	EU StageV	EU StageV
	7.2	Engine power according to DIN ISO 1585	kw	32.8	38.4	34	38	38.4	34	38	43.4	44.8	43.4	44.8	43.4	44.8	43.4	44.8
	7.3	Rated speed	min	2450	2700	2400	2400	2700	2400	2400	2700	2400	2700	2400	2700	2400	2700	2400
	7.4	Number of cylinders/displacement	(-)/(cm³)	4/2659	4/2065	3/2227	4/2615	4/2065	3/2227	4/2615	4/2488	3/2230	4/2488	3/2230	4/2488	3/2230	4/2488	3/2230
	7.10	Battery voltage/nominal capacity	V/Ah	12/60	12/60	12/90	12/90	12/60	12/90	12/60	12/60	12/90	12/60	12/90	12/60	12/90	12/60	12/90
		Rated torque	N·m/r/min	142/1600	151/1600	150/1600-1800	174.1/1500	142/1600	150/1600-1800	174.1/1500	183.5/1600	210/1600-1800	188/1600	210/1600-1800	188/1600	210/1600-1800	188/1600	210/1600-1800
		Bore x stroke	mm	92x100	89x83	94x107	87x110	92x100	94x107	87x110	89x100	94x107	89x100	94x107	89x100	94x107	89x100	94x107
		Transmissions Manufacturer		REDDOT/OKAMURA	REDDOT/OKAMURA	REDDOT	REDDOT	REDDOT/OKAMURA	REDDOT	REDDOT	REDDOT/OKAMURA	REDDOT/OKAMURA	REDDOT/OKAMURA	REDDOT/OKAMURA	REDDOT/OKAMURA	REDDOT/OKAMURA	REDDOT/OKAMURA	REDDOT/OKAMURA
		Transmissions Type		Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift
Addition data		Stage FWD/RVS		1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1
	10.1	Operating pressure for attachments	bar	145	145	145	145	145	145	145	175	175	175	175	175	175	175	175
	10.4	Fuel tank capacity	liter	50	28	50	50	28	50	50	40	60	40	60	40	70	40	70

Note : *With suspension seat or cabin
* As a calculated value

Optional Engine / Transmission

Engine	Engine manufacturer/type		GCT K21			YANMAR 4TNE92		GCT K21 LPG		GCT GK21 LPG	GCT GK21 LPG EU StageV	GCT GK21 LPG 1G001 EKH00	GCT GK21 DUAL 1G001 ECH00	KUBOTA V2607-CR-E5B	YANMAR 4TNE98	XINCHAI A498BT1	GCT K25 LPG	GCT GK25LPG	GCT K25	mitsubishi 54S-DPEU2	ISUZU 4JG2PE-01	GCT GK25 LPG EU StageV	XINCHAI 3E22YG51P464	XINCHAI 3E22YG51	KUBOTA V2607-CR-TE5B	GCT GK25 LPG 1G001 ELH00	GCT GK25 DUAL 1G001 EDH00		
	Manufacturer's type designation		W21			W32		W51		W87	H1	H23	H24		W97	W33	W27	W52	W77	W22	W55	W13	H3	H7	H7	W98	H21	H22	
	Drive		Gasoline	Gasoline/ DUAL FUEL/ LPG	Gasoline/ DUAL FUEL/ LPG	Diesel	LPG		LPG	LPG	LPG	DUAL LPG/GAS		Diesel	Diesel	Diesel	LPG	LPG	Gasoline DUAL FUEL/LPG	Diesel	Diesel	LPG	Diesel	Diesel	Diesel	LPG	DUAL LPG/GAS		
	Emission STD		——			StageIIIA		——		——		EU StageV		CARB SIP LSI-1/ EPA Tier2/ EU STAGE V		Stage V/Tier 4F		StageIIIA	StageIIIA	——	——	——	StageIIIA	StageII	EU StageV	EU StageV	EU StageV	EU StageV EPA/CARB Tier4 F	CARB SIP LSI-1/ EPA Tier2/ EU STAGE V
	Engine power		kW/r/min	31.2/2250			32.8/2450		29/2250		38.4/2700	38.4/2700	43/2700	43/2700 40/2700	38/2400	42.1/2300	36.8/2400	35/2400	43.4/2700	37.4/2500	35.3/2250	46/2450	43.4/2700	34/2400	44.8/2400	47.3/2400	47/2700	47/2700 44.5/2700	
	Rated torque		N·m/r/min	143.7/1600			149/1600		140/1600		151/1600	151/1600	161/1800	161/1800 153/1800	174.1/1500	206/1700	186/1600~1800	170/1600	183.5/1600	176.5/1600	177/1700	186/1700±100	183.5/1600	150/1600~1800	210/1600~1800	221.7/1500	190/1600	190/1600 175/1600	
	Number of cylinders/displacement		ml	4/2065			4/2659		4/2065		4/2065	4/2065	4/2065	4/2065	4/2615	4/3319	4/3168	4/2488	4/2488	4/2488	4/3331	4/3059	4/2488	3/2227	3/2230	4/2615	4/2488	4/2488	
Transmission	Powershift	F(CHINA)	F	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓		
		OKAMURA(JAPAN)	B	✓	✓	✗	✓	✗	✓	✗	✓	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓	✗	✓	✓	✗	✓	✓		
Rated capacity/rated load			Q (kg)	1000	1500-1750	2000	1000-1750	2000-2500	1500-1750	2000-2500	1500-1750	1500-1750	1500-1750	1500-3500	2000-3500	2000-3500	2000-3500	2000-3500	2000-3500	2000-3500	3000-3500	2000-3500	1500-1800	2000-3500	2000-3500	2000-3500	2000-3500		




XF series 1.5-3.5t forklift specification:

Distinguishing mark	1.1	Importer		KELVIN											
	1.2	Manufacturer's type designation		CPYD15-XH23F/B1	CPYD18-XH23F/B1	CPYD20-XH21F/B1	CPYD25-XH21F/B1	CPYD30-XH21F/B1	CPYD35-XH21F/B1	CPQYD15-XH24F/B1	CPQYD18-XH24F/B1	CPQYD20-XH22F/B1	CPQYD25-XH22F/B1	CPQYD30-XH22F/B1	CPQYD35-XH22F/B1
	1.3	Drive: electric (battery or mains), diesel, petrol, fuel gas		LPG	LPG	LPG	LPG	LPG	LPG	LPG/GAS	LPG/GAS	LPG/GAS	LPG/GAS	LPG/GAS	LPG/GAS
	1.5	Rated capacity/rated load	Q (kg)	1500	1750	2000	2500	3000	3500	1500	1750	2000	2500	3000	3500
	1.6	Load centre distance	c (mm)	500	500	500	500	500	500	500	500	500	500	500	500
	1.8	Load distance, centre of drive axle to fork	x (mm)	405	405	465	465	480	485	405	405	465	465	480	485
		Rear overhang	mm	405	430	415	490	550	615	405	430	415	490	550	615
	1.9	Wheelbase	y (mm)	1475	1475	1650	1650	1700	1700	1475	1475	1650	1650	1700	1700
Weight	2.1	Service Weight	kg	2650	2760	3405	3765	4350	4705	2650	2760	3405	3765	4350	4705
	2.2	Axle loading, laden front/rear	kg	3660/490	3995/520	4705/700	5475/790	6450/900	7255/950	3660/490	3995/520	4705/700	5475/790	6450/900	7255/950
	2.3	Axle loading, unladen front/rear	kg	1240/1410	1225/1540	1610/1795	1560/2205	1750/2600	1720/2985	1240/1410	1225/1540	1610/1795	1560/2205	1750/2600	1720/2985
Tyres, chassis	3.2	Tyre size, front		6.50-10-10PR	6.50-10-10PR	7.00-12-12PR	7.00-12-12PR	28×9-15-14PR	28×9-15-14PR	6.50-10-10PR	6.50-10-10PR	7.00-12-12PR	7.00-12-12PR	28×9-15-14PR	28×9-15-14PR
	3.3	Tyre size, rear		5.00-8-10PR	5.00-8-10PR	6.00-9-10PR	6.00-9-10PR	6.50-10-10PR	6.50-10-10PR	5.00-8-10PR	5.00-8-10PR	6.00-9-10PR	6.00-9-10PR	6.50-10-10PR	6.50-10-10PR
	3.6	Tread, front	b10 (mm)	900	900	965	965	1005	1005	900	900	965	965	1005	1005
	3.7	Tread, rear	b11 (mm)	920	920	973	973	975	975	920	920	973	973	975	975
Dimensions	4.1	Tilt of mast/fork carriage forward/backward	α/β(°)	6/12	6/12	6/12	6/12	6/12	6/12	6/12	6/12	6/12	6/12	6/12	6/12
	4.2	Height, mast lowered	h1 (mm)	1995	1995	2035	2035	2050	1995	2165	1995	2035	2035	2050	2165
	4.3	Free lift	h2 (mm)	155	155	140	140	145	145	155	155	140	140	145	145
	4.4	Lift	h3 (mm)	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000
	4.5	Height, mast extended	h4 (mm)	3955	3955	4045	4045	4145	4145	3955	3955	4045	4045	4145	4145
	4.7	Height of overhead guard (cabin)	h5 (mm)	2125(2205*)	2125(2205*)	2135(2215*)	2135(2215*)	2150(2230*)	2150(2230*)	2125 (2205*)	2125(2205*)	2135(2215*)	2135(2215*)	2150(2230*)	2150(2230*)
	4.20	Length to face of forks	l2 (mm)	2285	2310	2530	2605	2730	2800	2285	2310	2530	2605	2730	2800
	4.21	Overall width	b1 (mm)	1080	1080	1155	1155	1225	1225	1080	1080	1155	1155	1225	1225
	4.22	Fork dimensions	s/e/l (mm)	920×100×35	920×100×35	1070×122×40	1070×122×40	1070×122×45	1070×122×50	920×100×35	920×100×35	1070×122×40	1070×122×40	1070×122×45	1070×122×50
	4.31	Ground clearance, laden, below mast	m1 (mm)	115	115	115	115	130	130	115	115	115	115	130	130
	4.32	Ground clearance, centre of wheelbase	m2 (mm)	140	140	150	150	165	165	140	140	150	150	165	165
	4.35	Turning radius	Ws (mm)	1990	2015	2180	2245	2355	2415	1990	2015	2180	2245	2355	2415
		Min. right angle stacking aisle width (Add load length and clearance)	mm	2395	2420	2645	2710	2835	2900	2395	2420	2645	2710	2835	2900
Performance data	5.1	Travel speed, laden/unladen	km/h	(-/20)	(-/20)	(-/20)	(-/20)	(-/19.8)	(-/19.8)	(-/20)	(-/20)	(-/20)	(-/20)	(-/19.8)	(-/19.8)
	5.2	Lift speed, laden/unladen	m/s	0.530/-	0.530/-	0.560/-	0.560/-	0.480/-	0.480/-	0.530/-	0.530/-	0.560/-	0.560/-	0.480/-	0.480/-
	5.3	Lowering speed, laden/unladen	m/s	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-
	5.5	Drawbar pull, laden/unladen	N	(17500/-)	(17500/-)	(21000/-)	(21000/-)	(22000/-)	(22000/-)	(17500/-)	(17500/-)	(21000/-)	(21000/-)	(22000/-)	(22000/-)
	5.7	Gradeability, laden/unladen*	%	(37/-)	(37/-)	(30/-)	(30/-)	(25/-)	(25/-)	(37/-)	(37/-)	(30/-)	(30/-)	(25/-)	(25/-)
Combustion-engine	7.1	Engine manufacturer/type		GCT GK21 LPG	GCT GK21 LPG	GCT GK25 LPG	GCT GK25 LPG	GCT GK25 LPG	GCT GK25 LPG	GCT GK21 DUAL	GCT GK21 DUAL	GCT GK25 DUAL	GCT GK25 DUAL	GCT GK25 DUAL	GCT GK25 DUAL
		Emission STD		CARB SIP LSI-1/ EPA Tier2/ EU StageV	CARB SIP LSI-1/ EPA Tier2/ EU StageV	CARB SIP LSI-1/ EPA Tier2/ EU StageV	CARB SIP LSI-1/ EPA Tier2/ EU StageV	CARB SIP LSI-1/ EPA Tier2/ EU StageV	CARB SIP LSI-1/ EPA Tier2/ EU StageV	CARB SIP LSI-1/ EPA Tier2/ EU StageV	CARB SIP LSI-1/ EPA Tier2/ EU StageV	CARB SIP LSI-1/ EPA Tier2/ EU StageV	CARB SIP LSI-1/ EPA Tier2/ EU StageV	CARB SIP LSI-1/ EPA Tier2/ EU StageV	CARB SIP LSI-1/ EPA Tier2/ EU StageV
	7.2	Engine power according to DIN ISO 1585	kw	43	43	47	47	47	47	43/40	43/40	47/44.5	47/44.5	47/44.5	47/44.5
	7.3	Rated speed	min	2700	2700	2700	2700	2700	2700	2700	2700	2700	2700	2700	2700
	7.4	Number of cylinders/displacement	(-)/(cm³)	4/2065	4/2065	4/2488	4/2488	4/2488	4/2488	4/2065	4/2065	4/2488	4/2488	4/2488	4/2488
	7.10	Battery voltage/nominal capacity	V/Ah	12/60	12/60	12/60	12/60	12/60	12/60	12/60	12/60	12/60	12/60	12/60	12/60
		Rated torque	N·m/r/min	161/1800	161/1800	190/1600	190/1600	190/1600	190/1600	(161/1800)/(153/1800)	(161/1800)/(153/1800)	(190/1600)/(175/1600)	(190/1600)/(175/1600)	(190/1600)/(175/1600)	(190/1600)/(175/1600)
		Bore × stroke	mm	89×83	92×100	89×100	89×100	89×100	89×100	89×83	92×100	89×100	89×100	89×100	89×100
		Transmissions Manufacturer		REDDOT/OKAMURA	REDDOT/OKAMURA	REDDOT/OKAMURA	REDDOT/OKAMURA	REDDOT/OKAMURA	China/OKAMURA	China/OKAMURA	China/OKAMURA	China/OKAMURA	China/OKAMURA	China/OKAMURA	China/OKAMURA
		Transmissions Type		Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift
		Stage FWD/RVS		1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1
Addition data	10.1	Operating pressure for attachments	bar	145	145	175	175	175	175	145	145	175	175	175	175
	10.4	Fuel tank capacity	liter	NA	NA	NA	NA	NA	NA	28	28	40	40	40	40

Note : *With suspension seat or cabin
* As a calculated value

Optional Engine / Transmission

Engine	Engine manufacturer/type		GCT K21			YANMAR 4TNE92		GCT K21 LPG		GCT GK21 LPG	GCT GK21 LPG EU StageV	GCT GK21 LPG 1G001 EKH00	GCT GK21 DUAL 1G001 ECH00	KUBOTA V2607-CR-E5B	YANMAR 4TNE98	XINCHAI A498BT1	GCT K25 LPG	GCT GK25LPG	GCT K25	mitsubishi S4S-DPEU2	ISUZU 4JG2PE-01	GCT GK25 LPG EU StageV	XINCHAI 3E22YG51P464	XINCHAI 3E22YG51	KUBOTA V2607-CR-TE5B	GCT GK25 LPG 1G001 ELH00	GCT GK25 DUAL 1G001 EDH00																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
	Manufacturer's type designation		W21			W32		W51		W87	H1	H23	H24	W97	W33	W27	W52	W77	W22	W55	W13	H3	H7	H7	W98	H21	H22																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
	Drive		Gasoline	Gasoline/ DUAL FUEL/ LPG	Gasoline/ DUAL FUEL/ LPG	Diesel	LPG		LPG	LPG	LPG	DUAL LPG/GAS	Diesel	Diesel	Diesel	LPG	LPG	Gasoline DUAL FUEL/LPG	Diesel	Diesel	LPG	Diesel	Diesel	Diesel	Diesel	LPG	DUAL LPG/GAS																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
	Emission STD		——			StageIIIA		——		——		EU StageV		CARB SIP LSI-1/ EPA Tier2/ EU STAGE V		Stage V/Tier 4F	StageIIIA	StageIIIA	——	——	——	StageIIIA	StageII	EU StageV	EU StageV	EU StageV	EU StageV EPA/CARB Tier4 F	CARB SIP LSI-1/ EPA Tier2/ EU STAGE V																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																	
	Engine power		kW/r/min	31.2/2250			32.8/2450		29/2250		38.4/2700		38.4/2700		43/2700		43/2700 40/2700		38/2400		42.1/2300		36.8/2400		35/2400		43.4/2700		37.4/2500		35.3/2250		46/2450		43.4/2700		34/2400		44.8/2400		47.3/2400		47/2700		47/2700 44.5/2700																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
	Rated torque		N·m/r/min	143.7/1600			149/1600		140/1600		151/1600		151/1600		161/1800		161/1800 153/1800		174.1/1500		206/1700		186/1600~1800		170/1600		183.5/1600		176.5/1600		177/1700		186/1700±100		183.5/1600		150/1600~1800		210/1600~1800		221.7/1500		190/1600		190/1600 175/1600																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
	Number of cylinders/displacement		ml	4/2065			4/2659		4/2065		4/2065		4/2065		4/2065		4/2615		4/3319		4/3168		4/2488		4/2488		4/2488		4/3331		4/3059		4/2488		3/2227		3/2230		4/2615		4/2488		4/2488																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
Transmission	Powershift	F(CHINA)	F	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓



1.0~1.75t XF series mast: (pneumatic)

Type	Model	Max. fork height	Overall height			Free lift		Front Overhang		Tilt range		Capacity					
			Lowered	Extended		Without backrest	With backrest	1 / 1.5	1.75t	FWD	BWD	Load capacity at 500mm					
				Without backrest	With backrest							Single tire			Dual tire		
												1t	1.5t	1.75t	1t	1.5t	1.75t
		mm	mm	mm	mm	mm	mm	mm	(°)	(°)	kg	kg	kg	kg	kg	kg	
Wide view mast	X15M200	2000	1495	2565	2955	155	155	405	410	6	12	1000	1500	1750	1000	1500	1750
	X15M250	2500	1745	3065	3455	155	155	405	410	6	12	1000	1500	1750	1000	1500	1750
	X15M270	2700	1845	3265	3655	155	155	405	410	6	12	1000	1500	1750	1000	1500	1750
	X15M300	3000	1995	3565	3955	155	155	405	410	6	12	1000	1500	1750	1000	1500	1750
	X15M330	3300	2145	3865	4255	155	155	405	410	6	12	1000	1500	1750	1000	1500	1750
	X15M350	3500	2245	4065	4455	155	155	405	410	6	12	1000	1500	1750	1000	1500	1750
	X15M370	3700	2395	4265	4655	155	155	405	410	6	12	1000	1500	1750	1000	1500	1750
	X15M400	4000	2595	4600	4955	155	155	405	410	6	12	1000	1500	1650	1000	1500	1700
	X15M430	4300	2745	4900	5255	155	155	405	410	6	6	950	1450	1600	1000	1450	1650
	X15M450	4500	2845	5100	5455	155	155	405	410	6	6	900	1400	1550	950	1400	1600
	X15M470	4700	2945	5300	5655	155	155	405	410	6	6	850	1350	1500	900	1350	1550
	X15M500	5000	3095	5600	5955	155	155	405	410	6	6	800	1300	1450	850	1300	1500
	X15M550	5500	3345	6100	6455	155	155	405	410	6	6	/	/	/	750	1150	1300
	X15M600	6000	3595	6600	6955	155	155	405	410	6	6	/	/	/	700	1050	1150
Wide view full free duplex mast	X15U200	2000	1560	2585	2945	975	615	405	410	6	12	1000	1500	1750	1000	1500	1750
	X15U250	2500	1810	3085	3445	1225	865	405	410	6	12	1000	1500	1750	1000	1500	1750
	X15U270	2700	1910	3285	3645	1325	965	405	410	6	12	1000	1500	1750	1000	1500	1750
	X15U300	3000	2010	3590	3950	1425	1065	405	410	6	12	1000	1500	1750	1000	1500	1750
	X15U330	3300	2160	3885	4245	1575	1215	405	410	6	12	1000	1500	1750	1000	1500	1750
	X15U350	3500	2260	4085	4445	1675	1315	405	410	6	12	1000	1500	1750	1000	1500	1750
	X15U370	3700	2360	4285	4645	1775	1415	405	410	6	12	1000	1500	1750	1000	1500	1750
	X15U400	4000	2560	4585	4945	1975	1615	405	410	6	12	1000	1500	1650	1000	1500	1700
	X15N400	4000	1970	4680	4955	1300	1025	420	425	6	6	900	1400	1550	950	1400	1600
	X15N430	4300	2070	4980	5255	1400	1125	420	425	6	6	850	1350	1500	900	1350	1550
Wide view full free triplex mast	X15N450	4500	2120	5130	5455	1500	1175	420	425	6	6	800	1300	1450	850	1300	1500
	X15N470	4700	2170	5380	5750	1585	1225	420	425	6	6	750	1250	1400	800	1250	1450
	X15N500	5000	2270	5595	5955	1685	1325	420	425	6	6	700	1200	1350	800	1250	1450
	X15N550	5500	2470	6095	6455	1885	1525	420	425	3	6	650	950	1050	750	1150	1300
	X15N600	6000	2720	6730	7055	2100	1775	420	425	3	6	600	700	750	700	1050	1150
	X15N650	6500	2870	7180	7455	2200	1925	420	425	3	6	/	/	/	550	800	900
	X15N700	7000	2970	7595	7955	2385	2025	420	425	3	6	/	/	/	400	550	650

With sideshifter minus 150kg,with integral sideshifter minus 100kg.

2.0~2.5t XF series mast: (pneumatic)

Type	Model	Max. fork height	Overall height				Free lift		Front Overhang	Tilt range		Capacity			
			Lowered	Extended		Without backrest	With backrest	FWD		BWD	Load capacity at 500 mm				
				Without backrest	With backrest						Single tire		Dual tire		
											2.0t	2.5t	2.0t	2.5t	
		mm	mm	mm	mm	mm	mm	mm	(°)	(°)	kg	kg	kg	kg	
Wide view mast	X25M200	2000	1535	2660	3045	140	140	465	6	12	2000	2500	2000	2500	
	X25M250	2500	1785	3160	3545	140	140	465	6	12	2000	2500	2000	2500	
	X25M270	2700	1885	3360	3745	140	140	465	6	12	2000	2500	2000	2500	
	X25M300	3000	2035	3660	4045	140	140	465	6	12	2000	2500	2000	2500	
	X25M330	3300	2185	3960	4345	140	140	465	6	12	2000	2500	2000	2500	
	X25M350	3500	2285	4160	4545	140	140	465	6	12	2000	2500	2000	2500	
	X25M370	3700	2435	4360	4745	140	140	465	6	12	2000	2500	2000	2500	
	X25M400	4000	2635	4660	5045	140	140	465	6	12	2000	2500	2000	2500	
	X25M430	4300	2785	4960	5345	140	140	465	6	6	1950	2400	2000	2450	
	X25M450	4500	2855	5160	5545	140	140	465	6	6	1950	2300	1950	2350	
	X25M470	4700	2985	5360	5745	140	140	465	6	6	1850	2250	1900	2300	
	X25M500	5000	3135	5660	6045	140	140	465	6	6	1800	1850	1850	2100	
Wide view full free duplex mast	X25M550	5500	3385	6160	6545	140	140	465	3	6	/	/	1600	1900	
	X25M600	6000	3635	6660	7045	140	140	465	3	6	/	/	1400	1750	
	X25U200	2000	1560	2680	3045	880	510	465	6	12	2000	2500	2000	2500	
	X25U250	2500	1810	3180	3545	1130	760	465	6	12	2000	2500	2000	2500	
	X25U270	2700	1910	3380	3745	1230	860	465	6	12	2000	2500	2000	2500	
	X25U300	3000	2010	3680	4045	1330	960	465	6	12	2000	2500	2000	2500	
	X25U330	3300	2160	3980	4345	1480	1110	465	6	12	2000	2500	2000	2500	
	X25U350	3500	2260	4180	4545	1580	1210	465	6	12	2000	2500	2000	2500	
	X25U370	3700	2360	4380	4745	1680	1310	465	6	12	2000	2500	2000	2500	
	X25U400	4000	2560	4680	5045	1880	1510	465	6	12	2000	2450	2000	2500	
	X25N400	4000	2000	4700	5045	1300	955	480	6	6	1950	2450	1950	2500	
	X25N430	4300	2100	5000	5345	1400	1055	480	6	6	1900	2400	1950	2450	
Wide view full free triplex mast	X25N450	4500	2150	5230	5595	1470	1105	480	6	6	1850	2300	1850	2300	
	X25N470	4700	2200	5380	5745	1520	1155	480	6	6	1800	2250	1800	2300	
	X25N500	5000	2300	5680	6045	1620	1255	480	6	6	1700	1900	1800	2100	
	X25N550	5500	2500	6180	6545	1820	1455	480	3	6	1450	1600	1600	1900	
	X25N600	6000	2750	6730	7095	2070	1705	480	3	6	1000	1050	1200	1750	
	X25N650	6500	2900	7200	7545	2200	1855	480	3	6	/	/	1200	1450	
	X25N700	7000	3050	7680	8045	2370	2005	480	3	6	/	/	1000	1150	

With sideshifter minus 150kg,with integral sideshifter minus 100kg.

3.0~3.5t XF series mast: (pneumatic)

Type	Model	Max. fork height	Overall height
------	-------	------------------	----------------